



Trinahome T Series (NCA Type Battery)

Trina Energy Storage Solutions for New Residential Installations



PV & Battery Hybrid System

**Rated Power: 5.2 kW, 9.8 kW
(Three-phase)**



**Capacity: 6 kWh - 18 kWh
(Expandable in steps of 3 kWh)**

**Warranty: 10 years Battery Performance
(Expected lifetime 20 years)**



Plug & Play



Backup Possible



Visualisation



Self-Consumption



Modular Customised



Easy Installation



Reliable Performance



Proven Safety

China:
Trina Energy Storage Solutions (Jiangsu) Co., Ltd.
Tel: +86 519 8517 6686
Email: trinabess@trinagroup.com
Add: No. 2 Tianhe Road, Trina PV Park,
New District, Changzhou, Jiangsu






Germany:
Trina Energie Storage Vertrieb und Service GmbH
Tel: +49 (0) 69 75844 361
Email: eu.sales@trinabess.com
Add: Otto-Schott-Str. 4, 60438,
Frankfurt am Main, Germany

Oceania:
Trina Energy Storage Solutions (Australia) Pty. Ltd.
Tel: +61 2 9199 8504
Email: australia.sales@trinabess.com
Add: 44.05, Level 44, 1 Farrer Place Sydney,
NSW, 2000

Japan:
Trina Energy Storage Japan Co., Ltd.
Tel: +81 (0) 3 6432 0581
Email: jp.sales@trinabess.com
Add: 21F World Trade Center Building,
4-1, 2-chome, Hamamatsu-cho,
Minato-ku, Tokyo 105-6121 Japan

Hybrid Inverter	TB5200TD	TB9800TH
PV Input		
Max. PV Input Power / Max. PV Array Size	5200 W / 6800 W	9800 W / 12800 W
Max. PV Voltage	800 V	900 V
MPP Voltage Range	150 - 700 V	200 - 800 V
MPP Tracker	2	2
Max. Input Current	2 * 11 A	2 * 14 A
Max. Short-circuit Current, Module Array	2 * 13.8 A	2 * 17.5 A
Start PV Voltage	200 V	300 V
Battery Input (DC)		
Max. Charging / Discharging Power*	4000 W / 4000 W	8000 W / 8000 W
Max. Charging / Discharging Current	18 A / 18 A	20 A / 20 A
Operation Voltage Range	120 - 500 V	200 - 800 V
Battery Full Power Voltage Range	222 - 500 V	400 - 800 V
AC Output		
Max. Output Power	5000 W	9600 W
Rated Output Voltage	3N - 400 Vac	
Rated Output Frequency	50 Hz	
AC Nominal Current	7.2 A	13.9 A
Back-up Function Possible (optional, need an additional external backup switch box)		
Max. Auto-switching Time	< 5 Seconds	
AC Voltage L - L	324 V - 436 V	
AC Rated Frequency	50 Hz	
Max. Backup Supply Power	2.5 kVA	4.8 kVA
Other Parameters		
Max. efficiency (PV - battery - grid)	≥ 91 %	≥ 91 %
Europ. efficiency (PV - grid)	≥ 95 %	≥ 95 %
IP Protection Class	IP 65	
Noise	< 55 dB	
Dimension (W x H x D)	470 x 600 x 230 mm	540 x 670 x 270 mm
Weight	< 40 kg	< 55 kg
Cooling	Forced Air Cooling	
Certificate	VDE 4105, IEC 62109, IEC 62477	

Battery Packs

Nominal Voltage	200 V	300 V	400 V	500 V	600 V
Applicable System	TB5200TD	TB5200TD / TB9800TH	TB5200TD / TB9800TH	TB9800TH	TB9800TH
Usable Battery Capacity	2 * 3 kWh	3 * 3 kWh	4 * 3 kWh	5 * 3 kWh	6 * 3 kWh
Single Module / Control Box Weight	< 30 kg / 10 kg				
Module Appearance and Dimension (W x H x D) / Weight	 720 x 600 x 190 mm < 70 kg	 720 x 820 x 190 mm < 100 kg	 720 x 1040 x 190 mm < 130 kg	 720 x 1260 x 190 mm < 160 kg	 720 x 1480 x 190 mm < 190 kg
Other Parameters					
Battery Cell	NCA				
DOD	100 %				
Cycle Life	> 8000				
Communication	CAN2.0				
Certificate	UN 38.3, CE				
IP Protection Class	IP 55				

System

Humidity	0 ~ 95 %
Operating Temperature Range	-10 ~ 45 °C (-10 ~ 0 °C with derating)
Warranty	5 years product, 10 years battery performance

* The actual Max. charging / discharging will be depending on different output voltage of connected battery bank.

CAUTION: READ SAFETY AND INSTALLATION INSTRUCTIONS BEFORE USING THE PRODUCT.

