


SIV SERIES

Small Changes, Big Accomplishments

390-405w



• SIV SERIES

Seraphim redefined the high-efficiency module series by integrating 182mm silicon wafers with multi-busbar and half-cut cell technologies. Seraphim panel combined creative technology effectively and extremely improved the module efficiency and power output.

• KEY FEATURES

-  Less mismatch to get more power
-  Less power loss by minimizing the shading impact
-  Competitive low light performance
-  3 times EL test to ensure best quality
-  Ideal choice for utility and commercial scale projects by reduced BOS and improve ROI
- PVEL** Outstanding reliability proven by PVEL for stringent environment condition :
 - sand, acid, salt, and hail stones
 - 2400pa wind load and 5400pa snow load
 - Anti-PID

• QUALITY SYSTEM

ISO19001 / ISO14001 / OHSAS18001


• PRODUCT CERTIFICATION



• INSURANCE

PICC

• WARRANTY



Guarantee on product material and workmanship



linear power output warranty



JIANGSU SERAPHIM SOLAR SYSTEM CO., LTD

Add: No.1-2, HengyaoRd, HenglinTown, Wujin District, 213000, Changzhou, China
 Tel: +86-519-69699879 Fax: +86-519-88786181 Email: info@seraphim-energy.com

Electrical Characteristics

Module Type	SRP-390-BMD-HV	SRP-395-BMD-HV	SRP-400-BMD-HV	SRP-405-BMD-HV
	STC	STC	STC	STC
Maximum Power at STC (Pmp)	390	395	400	405
Open Circuit Voltage (Voc)	36.90	37.01	37.12	37.22
Short Circuit Current (Isc)	13.40	13.50	13.60	13.70
Maximum Power Voltage (Vmp)	30.59	30.69	30.81	30.93
Maximum Power Current (Imp)	12.78	12.88	12.99	13.10
Module Efficiency at STC(η_m)	20.17	20.42	20.68	20.94
Power Tolerance	(0,+3%)			
Maximum System Voltage	1500V DC			
Maximum Series Fuse Rating	25 A			

STC: Irradiance 1000 W/m² module temperature 25°C AM=1.5

Power measurement tolerance: +/-3%

Temperature Characteristics

Pmax Temperature Coefficient	-0.35 %/°C
Voc Temperature Coefficient	-0.27 %/°C
Isc Temperature Coefficient	+0.05 %/°C
Operating Temperature	-40 ~ +85 °C
Nominal Operating Cell Temperature (NOCT)	45±2 °C

Mechanical Specifications


External Dimensions	1707 x 1133 x 35 mm
Weight	21 kg
Solar Cells	PERC Mono (108pcs)
Front Glass	3.2 mm AR coating tempered glass, low iron
Frame	Anodized aluminium alloy
Junction Box	IP68, 3 diodes
Output Cables	4.0 mm ² , Portrait: 255mm(+)/355mm(-); Landscape: 1200mm
Mechanical Load	Front side 5400Pa/ Rear side 2400Pa

Packing Configuration

	1707 x 1133 x 35 mm	
Container	20'GP	40'HQ
Pieces per Pallet	31+4*	31
Pallets per Container	6	26
Pieces per Container	210	806

* 31+4 pieces per pallet is the special package which only suits for container transport

For details, please consult info SERAPHIM



I-V Curve

